

## 1. PRODUCT AND COMPANY IDENTIFICATION

### 1.1 Product identifiers

Product name : Xylenes  
Synonyms : Xylenes - Mixed Isomers Xylenes-Ethylbenzene Mixture Xylene Ethylbenzene Mixture

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Industrial use resulting in manufacture of another substance (use of intermediates)  
Solvent Fuel

### 1.3 Details of the supplier of the safety data sheet

Distributor : Continental Industries Group, Inc.  
733 Third Avenue Fl. 20  
Tel: 212-752-2020  
New York, NY 10017  
USA

### 1.4 Emergency telephone number

Chemtel Phone # : 1-800-255-3924  
International Phone # : +01-813-248-0585  
Contract # : MIS0001728

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids Category 3  
Skin corrosion/irritation Category 2  
Serious eye damage/eye irritation Category 2B  
Carcinogenicity Category 2  
Reproductive toxicity Category 2  
Specific target organ toxicity (single exposure) Category 3 - Narcotic effects  
Specific target organ toxicity (single exposure) Category 3 - Respiratory irritation  
Specific target organ toxicity (single exposure) Category 1  
Specific target organ toxicity (repeated exposure) Category 1  
Specific target organ toxicity (repeated exposure) Category 2  
Aspiration hazard Category 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s) : **Flammable liquid and vapor**  
**May be fatal if swallowed and enters airways**  
**Causes skin irritation**  
**Causes eye irritation**  
**May cause respiratory irritation**  
**May cause drowsiness or dizziness**  
**Suspected of causing cancer (inhalation)**

---

## 2. HAZARDS IDENTIFICATION cont'd

Hazard statement(s)	<b>Suspected of damaging fertility or the unborn child</b> <b>Causes damage to organs (lung) (inhalation, oral)</b> <b>Causes damage to organs (nervous system) through prolonged or repeated exposure (inhalation)</b> <b>May cause damage to organs (kidneys, hearing organ (loss of hearing)) through prolonged or repeated exposure</b>
Precautionary statement(s)	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe gas, mist, vapors. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection, flame retardant protective clothing, protective gloves. Specific treatment (see Section 4.1 of SDS or information on this label). If swallowed: Immediately call doctor, poison center. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with plenty of water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. In case of fire: Use carbon dioxide (CO <sub>2</sub> ), dry chemical, foam, Water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS -

Product can accumulate electrostatic charges that may cause fire by electrical discharges.

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances Not applicable

### 3.2 Mixture

Name	CAS No	%
Xylenes (o-, m-, p- isomers)	1330-20-7	>= 80
Ethylbenzene	100-41-4	<= 20
Toluene	108-88-3	<= 0.5

---

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

---

#### 4. FIRST AID MEASURES cont'd

- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.
- Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.
- Symptoms/injuries after eye contact : Causes eye irritation. Redness of the eye tissue.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

#### 5. FIREFIGHTING MEASURES

##### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

##### 5.2. Special hazards arising from the chemical

- Fire hazard : Flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Hazardous decomposition products in case of fire : Carbon oxides (CO, CO<sub>2</sub>). Soot. Toxic fumes.

##### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

---

#### 6. ACCIDENTAL RELEASE MEASURES

##### 6.1. Personal precautions, protective equipment and emergency procedures

- Emergency procedures for non-emergency personnel : Evacuate unnecessary personnel.
- Emergency procedures for emergency responders : Ventilate area.

##### 6.2. Methods and material for containment and cleaning up

- For containment : Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite. Do not contaminate ground and surface water.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

##### 6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

---

#### 7. HANDLING AND STORAGE

##### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

## 7. HANDLING AND STORAGE cont'd

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No bare lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Explosion-proof apparatus have to be used. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment. All efforts should be made to prevent any leaks or spills. Storage tanks should be engineered to prevent contact with water resources, as this material could contaminate the water resources. Surface spills can reach groundwater through porous soil or cracked surfaces. The storage tanks should be monitored regularly for leaks. Where spills or leaks are possible, a comprehensive response plan should be developed and implemented.

Storage conditions : Keep container tightly closed in a cool, well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, flames, sparks, heat sources. Keep container tightly closed.

Incompatible products : Strong oxidizing agents. Strong reducing agents. Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Occupational Exposure Limits

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
<b>Ethylbenzene (100-41-4)</b>		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
<b>Toluene (108-88-3)</b>		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
USA OSHA	Remark (OSHA)	See OSHA Table Z-2.

### 8.2. Exposure controls

Appropriate engineering controls : Use engineering controls, such as enclosed handling systems and local exhaust ventilation, as primary measures to prevent direct exposure to this material. Provide readily accessible eye wash stations and safety showers.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear Protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear fire/flame resistant/retardant clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

Other information : Do not eat, drink or smoke during use.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES cont'd

### 9.1 Information on basic physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Color	: Colorless.
Odor	: Sweet. Aromatic.
Odor threshold	: 0.7 - 40 ppm
pH	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: 9
Melting point	: No data available
Freezing point	: -47 °C
Boiling point	: 139 °C
Flash point	: 25 °C Closed cup
Auto-ignition temperature	: 500 - 550 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 8 mm Hg @ 25°C
Relative vapor density at 20 °C	: 3 - 4 Air = 1
Relative density	: 0.86
Specific gravity / density	: 0.87 g/ml @ 20°C
Solubility	: Water: Negligible.
Log Kow	: 3.1
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: 0.6 cP @25°C
Explosive limits	: 1 - 7 vol %

#### 9.2. Other information

VOC content	: 100 %
-------------	---------

---

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

### 10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous polymerization will not occur. Violent explosion may occur when chlorinating xylene with 1,3-dichloro-5,5-dimethyl-2, 4-imidazolidindione (dichlorohydrantoin). The haloimide undergoes immediate self accelerating decomposition.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks. Avoid the build-up of electrostatic charge.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: carbon monoxide, carbon dioxide, toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Likely routes of exposure	: Inhalation. Ingestion. Skin and eye contact.
Acute toxicity	: Not classified Inhalation at very high concentrations can be fatal. Intentional misuse involving repeated and prolonged inhalation exposure to high concentrations of vapor can result in central nervous system damage and eventually death.

<b>Xylene</b>	
LD50 oral rat	> 3500 (3500 - 4300) mg/kg as mixed xylenes containing ethylbenzene
LD50 dermal rabbit	> 4200 mg/kg as mixed xylenes containing ethylbenzene
LC50 inhalation rat	21.7 (21.7 - 29.1) mg/l/4h as mixed xylenes containing ethylbenzene
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer (inhalation).
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not classifiable
<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Toluene (108-88-3)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation. Causes damage to organs (lung) (inhalation, oral).
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (nervous system) through prolonged or repeated exposure (inhalation). May cause damage to organs (kidneys, hearing organ (loss of hearing)) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Harmful in contact with skin. Harmful if inhaled.

## 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
-------------------	--

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
<b>Ethylbenzene (100-41-4)</b>	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	4.6 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
EC50 other aquatic organisms 2	> 438 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
<b>Toluene (108-88-3)</b>	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])

---

## 12. ECOLOGICAL INFORMATION cont'd

### 12.2. Persistence and degradability

Xylene	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

Xylene	
Log Kow	3.1
Bioaccumulative potential	Not established.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15

Ethylbenzene (100-41-4)	
BCF fish 1	15
Log Pow	3.118

Toluene (108-88-3)	
Log Pow	2.65

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

---

## 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

---

## 14. TRANSPORT INFORMATION

NON-HAZARDOUS WHEN SHIPPED IN SMALL QUANTITIES IN A UN4G PACKAGE (WITH A STRONG OUTER PACKAGE) UNDER DOT 49 CFR 173.150(b)(3). OTHERWISE, IT IS CLASS 3, PG III UN 1993

### US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

Transport document description : UN1993, Flammable liquids, n.o.s. (contains xylene isomers, ethylbenzene), 3, PGIII

UN or NA Number : UN1993

Proper Shipping Name : Flammable liquids, n.o.s. (contains xylene isomers, ethylbenzene)

Primary Hazard Class : 3 - Flammable liquid

Packing Group : PGIII

Reportable Quantities (RQ)\* : Ethylbenzene 1000 lbs (454 kg), Mixed Xylenes 100 lbs (45.4 kg), Toluene 1000 lbs (454 kg)

\*It is the shipper's responsibility to determine whether an RQ must be reported for each individual shipment.

Hazard labels :



## 14. TRANSPORT INFORMATION

### Transport by sea (IMDG)

Transport document description : UN1993, FLAMMABLE LIQUID, N.O.S., 3, PGIII  
UN Number : UN1993  
Proper Shipping Name : Flammable liquid, n.o.s.  
Primary Hazard Class : 3 - Flammable liquids  
Packing Group : PGIII  
Hazard labels (IMDG) :



Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Product Name: Xylenes/Ethylbenzene (10% or more) mixture  
Pollution Category: Y  
Ship Type: 2

Cargo name listed in 46 CFR 30.25, Table 30.25-1 : Xylenes/Ethylbenzene (10% or more) mixture

Cargo name listed in 46 CFR 153, Table 1 : Xylenes, Ethylbenzene (10% or more) mixture

### Air transport (IATA)

Transport document description : UN1993, Flammable liquid, n.o.s., 3, PGIII  
UN Number : UN1993  
Proper Shipping Name : Flammable liquid, n.o.s.  
Primary Hazard Class : 3 - Flammable Liquids  
Packing Group : PGIII  
Hazard labels (IATA) :



## 15. REGULATORY INFORMATION

### 15.1. US Federal regulations

#### EPA TSCA Status

All components of this product are listed or excluded from listing on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

#### SARA Section 313 Supplier Notification

This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

CAS number	Chemical name	Concentration
1330-20-7	Xylenes (o-, m-, p- isomers)	>= 80%
100-41-4	Ethylbenzene	<= 20%

This information must be included in all Safety Data Sheets that are copied and distributed for this product. For additional information, see 40 CFR §372.45 Notification About Toxic Chemicals.

SARA Section 311/312 Hazard Classes : Fire hazard  
Chronic health hazard  
Acute health hazard

### 15.2. International regulations

#### CANADA

##### Xylene

WHMIS Classification : Class B Division 2 - Flammable Liquid  
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

---

## 15. REGULATORY INFORMATION

### National inventories

Listed on the Canadian DSL (Domestic Substances List)

### 15.3. US State regulations


<b>Ethylbenzene (100-41-4)</b>	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
No significance risk level (NSRL)	54 µg/day (inhalation)
<b>Toluene (108-88-3)</b>	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

---

## 16. OTHER INFORMATION

### NFPA (National Fire Protection Association)

NFPA health hazard : 2  
NFPA fire hazard : 3  
NFPA reactivity : 0



### HMIS III Rating

Health : 2\*  
Flammability : 3  
Physical Hazard : 0  
Personal Protection : See section 8 of SDS

### Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Continental Industries Group, Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

## 16. OTHER INFORMATION cont'd

US OSHA LABEL as specified under 29 CFR §1910.1200 (f)

### Xylene



#### Danger

**Flammable liquid and vapor**

**May be fatal if swallowed and enters airways**

**Causes skin irritation**

**Causes eye irritation**

**May cause respiratory irritation**

**May cause drowsiness or dizziness**

**Suspected of causing cancer (inhalation)**

**Suspected of damaging fertility or the unborn child**

**Causes damage to organs (lung) (inhalation, oral)**

**Causes damage to organs (nervous system) through prolonged or repeated exposure (inhalation)**

**May cause damage to organs (kidneys, hearing organ (loss of hearing)) through prolonged or repeated exposure**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical, lighting, ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe gas, mist, vapors.

Wash hands, forearms and face thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear eye protection, flame retardant protective clothing, protective gloves.

Specific treatment (see Section 4.1 of SDS or information on this label).

If swallowed: Immediately call doctor, poison center.

Do NOT induce vomiting.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry chemical, foam, Water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### **Supplemental Information: Other hazards not contributing to the classification**

Product can accumulate electrostatic charges that may cause fire by electrical discharges.

Continental Industries Group, Inc.  
733 Third Avenue Fl. 20  
Tel: 212-752-2020  
New York, NY 10017  
USA

#### **Emergency telephone number**

Chemtel Phone # : 1-800-255-3924  
International Phone # : +01-813-248-0585  
Contract # : MIS0001728